

GATE OPENER PLANNING GUIDE



NOTE: If you have a slide gate, or if your gate is LONGER THAN 18' or WEIGHS MORE THAN 850 lbs per leaf, ask your retailer about special order professional Gate Openers OR CALL 1-800-543-GATE

1. Select the Gate Opener best suited for your application:

MODEL #	GATE TYPE	SMART Capable	GATE LENGTH (PER LEAF)	WEIGHT (PER LEAF)	CAPACITY
MM571W	Single	Yes	UP TO 18'	UP TO 850 lbs	Heavy Duty
MM572W	Dual	Yes	UP TO 18'	UP TO 850 lbs	Heavy Duty
MM371W	Single	Yes	UP TO 16'	UP TO 550 lbs	Medium Duty
MM372W	Dual	Yes	UP TO 16'	UP TO 550 lbs	Medium Duty
MM271	Single	No	UP TO 12'	UP TO 300 lbs	Light Duty
MM272	Dual	No	UP TO 12'	UP TO 300 lbs	Light Duty
TS571W	Single	Yes	UP TO 18'	UP TO 850 lbs	Heavy Duty

Control and monitor your smart capable gate from anywhere with the Mighty Mule smartphone app and the MMS100 Wireless Connectivity System (sold separately).

2. How will you control the Gate?

Mighty Mule Gate Openers offer multiple ways to open and close your Gate Opener. Our new line of select smart capable Gate Openers offer the ability to control and monitor your gate from anywhere with the Mighty Mule app and the Wireless Connectivity System (part # MMS100 sold separately).

If you prefer to not add the Wireless Connectivity System, the gate can be opened or closed with the included entry/exit remote (part # MMT103). For guests entering your property that may not have a remote, a Mighty Mule Digital Keypad (part # MMK200) can be added to any Gate Opener.





3. How will you charge the battery: TRANSFORMER or SOLAR POWER?

All Mighty Mule Gate Openers are low voltage systems, powered by a 12 Volt battery back-up system. The battery can be charged and maintained with the included transformer or with optional part # FM123, 10 Watt Solar Panel Kit. If your gate is more than 1000 ft. from an AC power source, you must use solar power to charge the battery. See the cycles per day chart below to determine the Solar Power Kit needed for your application:



SINGLE GATE OPENER CYCLES PER DAY								
	10W	15W	20W	25W	30W			
ZONE 1	8	11	14	17	20			
ZONE 2	16	20	28	36	44			
ZONE 3	26 30		38	46	54			
DUAL GATE OPENERS CYCLES PER DAY								
ZONE 1	4	7	10	13	16			
ZONE 2	8	13	18	23	28			
ZONE 3	13	20	27	34	41			
DUAL GATE OPENERS REQUIRE A MINIMUM OF 10 WATTS								
Up to 30 watts of solar panel power can be added to any Mighty Mule Gate Opener system								



GATE OPENER PLANNING GUIDE

4.	Important installation considerations*:						
	produces a minimum of 250 cold cranking amps and battery box is required for operation of gate opener model		conductor, direct burial wire is also required for some accessories such as the 10 Watt Solar Panel (part #FM123) & wired Push Button Control (part # FM132).				
	#'s MM271,MM272, MM371W, MM372W & TS571W. A Mighty Mule 12 volt 7 amp hour battery is included with the gate opener models MM571W & MM572W.		If your gate opens away from your property due to a sloping driveway, then the Push To Open Bracket (part # FM148) is required for proper operation. Dual gate opene				
	Low Voltage Wire (part # RB509-100 or equivalent wire) is required for connecting the AC powered transformer to the control board. This 16 gauge, UV resistant, dual		require two Push To Open Brackets. Note: the MM271 & MM272 and not designed for Push To Open applications. *These items are not included with the gate opener kits.				
5.	Convenience and Security Options:	6.	The Installation:				
Please refer to the Mighty Mule catalog or visit MightyMule.com for accessory details and requirements.			Most installations can be completed easily in two to three hours. Each system includes online installation videos and easy-to-read instructions. The Mighty Mule Openers are				
Op	en Gate from Vehicle:		signed to be installed on new or existing driveway gates.				
	Three Button Entry/Exit Remote (part # MMT103) Digital Keypad (part # MMK200)		YOUR GATE MUST BE:				
	Wireless Connectivity System (part # MMS100) (works on Smart Gate Openers only)	A. Firmly hung on a well-seated fence post B. Swing freely and evenly					
	Push Button Control (part # FM132)	C.	Level and plumb, with no gate wheels				
	udo fue a Pulatinas	ADDITIONAL CONSIDERATIONS:					
Hands-free Exiting:		D. Ball Bearing hinges for gate over 250 lbs.					
	Wired Vehicle Exiting Sensor (part #s FM138, FM140 & FM141)		E. Gate posts thicker than 8" will require longer bolts (should be 2" longer than post thickness)				
☐ Wireless Vehicle Sensor (part # FM130-SW)			F. Gate posts less than 4"will require large metal washers or steel plates for reinforcing both sides of gate post.				
Securing the Gate:			G. Masonry columns require special procedures				
	Automatic Gate Lock (part # FM143)		(call 1-800-421-1587 for details)				
	Pin Lock (part # FM133)	Н.	Thin walled or panel gates may need reinforcement				
	Photo Beam Sensors (part # R4222)	то	OOLS YOU WILL NEED:				
Po	wering:	П	Power Drill				
П	10 Watt Solar Panel (part # FM123)		Phillips Screwdriver				
	Replacement Battery for MM571W & MM572W		Wire Strippers				
	Gate Openers (part # FM150)		Level				
	Low Voltage wire (part # RB509-100)		Tape Measure				
	Battery Heater for installations in cold climates		3/8" Drill Bit				
	(part # FM316)		Hacksaw or Heavy Duty Bolt Cutters				
На	rdware:		C-Clamps (small, medium AND large) Slotted (Flat Bladed) Screwdriver				
			Sibiled II lat Diaded/ Sciewariver				

TECHNICAL SUPPORT AND SALES: 1-800-421-1587 | www.MightyMule.com

☐ Open End Wrenches: 3/8", 7/16", 1/2", 9/16"

☐ Push to Open Bracket (FM148)